

# Rapier®

Industrial Type 3 fire hose with potable water capability

12  
MONTH  
WARRANTY



## Rapier - Now with Potable Water Capability

The trusted Rapier fire hose has been enhanced for even greater versatility. It features a robust TPU internal lining that's seamlessly bonded to its textile reinforcement - ensuring lasting strength and reliability in demanding conditions.

Its tough **PVC/Nitrile rubber blend outer cover** resists abrasion and wipes clean easily from oils, dirt, and grime. AS 2792 Type 3-certified fire hose in popular sizes, Rapier remains a go-to choice for fire brigades and industrial applications.

**New!** Rapier is now available with a blue lining that meets AS/NZS 4020 standards for safe drinking water use, making it ideal for temporary water bypass systems in municipal and mining environments.

This lightweight low-volume hose is available in **red**, with **yellow**, **blue**, and **Nato green** options to help distinguish between fire hose (red) and wash-down hose (blue) on the same industrial site. Rapier requires no drying, stores compactly, and is compatible with a wide range of securely fitted couplings. Some minimum order quantities may apply.

**Test certificates available** - so you can protect life, property, and water supply with confidence.

## FEATURES

- ✓ Abrasion resistant
- ✓ Synthetic - no drying
- ✓ High working pressure 2100 kPa
- ✓ Assembly & fittings available
- ✓ Potable water approved AS/NZS 4020
- ✓ Available in a variety of colours
- ✓ Easy to clean
- ✓ Australian Made
- ✓ Lightweight & quick to deploy

## TECHNICAL DATA

| Diameter (ID)                 | 25 mm         | 38 mm                 | 45 mm         | 51 mm                 | 64 mm         | 79 mm                 |
|-------------------------------|---------------|-----------------------|---------------|-----------------------|---------------|-----------------------|
|                               | 1"            | <b>1.5"</b>           | 1.75"         | <b>2"</b>             | 2.5"          | <b>3"</b>             |
| <b>Max. working pressure*</b> | 2100 kPa      | <b>2100 kPa</b>       | 2100 kPa      | <b>2100 kPa</b>       | 2100 kPa      | <b>1400 kPa</b>       |
| <b>Min. burst pressure</b>    | 5250 kPa      | <b>5250 kPa</b>       | 5250 kPa      | <b>5250 kPa</b>       | 5250 kPa      | <b>3500 kPa</b>       |
| <b>Weight/m</b>               | 0.19 kg       | <b>0.30 kg</b>        | 0.36 kg       | <b>0.43 kg</b>        | 0.56 kg       | <b>0.82 kg</b>        |
| <b>30 m coil diameter</b>     | 0.46 m        | <b>0.48 m</b>         | 0.48 m        | <b>0.48 m</b>         | 0.51 m        | <b>0.52 m</b>         |
| <b>AS 2792 approved</b>       | ✓             | ✓                     |               | ✓                     | ✓             |                       |
| <b>AN/NZS 4020 approved</b>   | ✓             | ✓                     | ✓             | ✓                     | ✓             | ✓                     |
| <b>Part # **</b>              | HHR025<br>XRA | <b>HHR038<br/>XRA</b> | HHR045<br>XRA | <b>HHR051<br/>XRA</b> | HHR064<br>XRA | <b>HHR079<br/>XRA</b> |

\*Dependent on maximum working pressure of attached couplings if lower.

\*\*Replace 8<sup>th</sup> character of part # for different colours: R = Red U = Blue Y = Yellow N = Nato Green

## Crusader Hose Pty Ltd

22 Industry Place, Bayswater VIC 3153 Australia

e: sales@crusaderhose.com.au p: +61 3 9720 1100

[www.crusaderhose.com.au](http://www.crusaderhose.com.au)

2507a

Crusader Hose reserves the right to modify any specification as part of ongoing product development and without prior notice.

Contact Crusader Hose to ensure that the current technical data sheets and documentation are used.

